





Application / Additional features



Type 80 AS and Type 80 AS-2: The spirit level is especially suitable for use in the fields

suitable for use in the fields of gardening and landscaping work, reinforced concrete

construction, carpentry as well as joinery and tiling. **Type 8o AS-2:** The **additional vertical vial** allows quick readings in any position.



Type 8o ASM: This spirit level is especially suitable for measuring tasks in metal construction and drywall construction. Extra-strong

rare-earth magnet system for adhesion to metal objects – leaves the hands free when aligning and adjusting pillars and supports (up to 5 times stronger than standard ferrite magnets).

Series 80 AS

Туре		80 AS		80 AS-2		8o ASM
Accuracy in normal position		0.029° = 0.5 mm/m		0.029° = 0.5 mm/m		0.029° = 0.5 mm/m
Accuracy in reverse position		0.043° = 0.75 mm/m		0.043° = 0.75 mm/m		0.043° = 0.75 mm/m
Measuring surfaces		2 X		2 X	_	2 X
Vial type		1 x horizontal 1 x vertical		1 x horizontal 2 x vertical		1 x horizontal 1 x vertical
End caps		Anti-slip stopper		Anti-slip stopper	_	Anti-slip stopper
Special feature		-		_		Rare-earth magnet
·						
Length	_	Art. No.		Art. No.		Art. No.
30 cm		19162				_
40 cm	1 # 480	19163	10	_	7 th 600	19177
50 cm	排棄用	19164	排棄性	\\ -	相重計	-
бо ст	U.S.	19165	400	19170	OLDE IN	19178
8o cm		19166		19171		19179
90 cm	<u>11</u>	19167	- 1	19195	£'	-
100 cm		19168		19172		19180
120 cm	- 1	19169	- 1	19173	2	19181
150 cm	00	-	D. 16	19174	100	19182
180 cm	16	_	10	19175	3	19183
200 cm	2	_	9	19176	鱼	19184
	-		parts.			
			=			