


Series 96 /196: For work with high demands


- Ultra-rigid aluminium profile with reinforcing ribs – for high stability and secure hold while working
- End caps with an anti-slip stopper – for a firm seat when marking
- Shock-absorbing end caps – the two-component material mix protects the profile against impact
- Removable end caps allow exact positioning and marking right up into the corners
- Easy to clean thanks to the electrostatic powder coating
- Spirit level with two precision-milled measuring surfaces (up to 122 cm, coated from 183 cm)
- Accurate measuring in all positions
- STABILA installation technology ensures long-term accuracy – suitable for measuring in normal and reverse position



Application / Additional features



Type 96-2 and Type 196-2: Especially suitable for craftsmen who subject their tools to extremely demanding conditions and need to measure in all positions; for example, in bricklaying and carpentry, in wood construction, reinforced concrete construction, window fitting, road construction, gardening and landscaping work.



Type 196-2: With **finger-grip openings** for easy and comfortable use.



Type 96-2-M: Especially suitable for measuring tasks in metal construction – the craftsman always has his hands free when aligning and adjusting components. **Rare-earth magnet system** – for extra-strong adhesion to metal objects.

Series 96 /196

Type	96-2	96-2 M	196-2	196-2 LED
Accuracy in normal position	0.029° = 0.5 mm/m	0.029° = 0.5 mm/m	0.029° = 0.5 mm/m	0.029° = 0.5 mm/m
Accuracy in reverse position	0.043° = 0.75 mm/m	0.043° = 0.75 mm/m	0.029° = 0.5 mm/m	0.029° = 0.5 mm/m
Measuring surfaces	2 x	2 x	2 x	2 x
Vial type	1 x horizontal 2 x vertical	1 x horizontal 2 x vertical	1 x horizontal 2 x vertical	1 x horizontal 2 x vertical
End caps	Anti-slip stopper / Shock-absorbing / Removable	Anti-slip stopper / Shock-absorbing / Removable	Anti-slip stopper / Shock-absorbing / Removable	Anti-slip stopper / Shock-absorbing / Removable
Special feature	–	Rare-earth magnet	–	LED
Length	Art. No.	Art. No.	Art. No.	Art. No.
40 cm	15225	15852	–	–
61 cm	15226	15853	15233	17392
81 cm	15227	15854	15234	–
100 cm	15228	15855	15235	–
122 cm	15229	15856	15236	17393
183 cm*	15230	15857	15237	–
200 cm*	15231	15858	17209	–
244 cm*	15232	–	–	–



Type 196-2 LED: For all craftsmen who often work in the dark or in poor visibility conditions and need to measure in all positions, especially when installing heating, in reinforced concrete construction or electrical installations. **Tough light technology that is suitable for use on construction sites** – for optimum readability.



Type 196-2 LED: Battery replacement pack with 2 LED units – quick lighting change at the workplace. Optional accessories (Art. No. 17450). Can also be used as a powerful mini torch.

* Continuous bridge over the horizontal vial increases the stability of the profile.